

## Axyia 5

Simply safe sterilization.

S-class autoclave Axyia 6 is designed around two core values: ease of use and durability. 4 programmes and automatic functions such as self-diagnosis, night cycle, cycle counter and remote control make it extremely easy to use. The choice of only quality materials and components guarantees maximum reliability over time. Elegant and compact, Axyia 6 weighs less than 20 kg and has a stainless steel chamber with a capacity of 6 litres.

Distributed by:







## STERILIZATION CYCLES

| Cycle       | Temperature | Sterilization | Drying   | Type of Cycle | Maximum    |
|-------------|-------------|---------------|----------|---------------|------------|
| 134° SOLID  | 134° C      | 4′            | 2' - 12' | S             | 1 - 1.4 kg |
| 134° POROUS | 134° C      | 14′           | 4' - 14' | S             | 0.2 kg     |
| 121° SOLID  | 121° C      | 20′           | 2' - 12' | S             | 1 - 1.4 kg |
| 121° POROUS | 121° C      | 30'           | 4' - 14' | S             | 0.2 kg     |

## **TECHNICAL CHARACTERISTICS**

|   | AXYIA 6   |  |  |
|---|---|--|--|
| OVERALL DIMENSIONS                                | 377 x 303 x 450 mm (L x H x D)  |  |  |
| CHAMBER DIMENSIONS                                | 170 X 276 mm (Ø X D)  |  |  |
| CHAMBER VOLUME                                    | 6.0 litres  |  |  |
| WEIGHT (empty)                                    | 21 kg   |  |  |
| POWER SUPPLY VOLTAGE                              | 230 V 50/60 Hz  |  |  |
| CONSUMPTION (power)                               | 400 W - 700 W   |  |  |
| OPERATING TEMPERATURE                             | +10 - +40°C   |  |  |
| OPERATING ALTITUDE (leaving the loading cap free) | between 0 and 2000 metres above sea level   |  |  |
| OPERATING RANGE                                   | Indoor use<br>Relative humidity 20 + 85%<br>Temperature +10 - +40°C<br>Atmospheric pressure 750 + 1050 mbar |  |  |
| VOLUME OF WATER CONSUMED                          | 0.3 litres  |  |  |
| TANK CAPACITY (clean water and used water)        | 2 litres each   |  |  |
| AUTOMATIC SWITCH-OFF                              | After 30' on standby at the end of the cycle  |  |  |





Distributed by:



Quantum Biomedical Services Sdn. Bhd. HQ: Unit L3A-6, Level 3A, Wisma Kemajuan, No. 2 Jalan 19/1b, 46300 Petaling Jaya, Selangor Darul Ehsan. Tel: 03-7629 6777 - Fax: 03-7629 6779 - Email: enquiries@qbms.com.my - Website: qbms.com.my

